



Can Bullet Characteristics Link a Bullet to a Manufacturer?

Brown A*

Albany State University, USA

*Corresponding author: Brown A, Albany State University, USA, Tel: +1-7068307144, E-mail: saraneab@yahoo.com

Citation: Brown A (2021) Can Bullet Characteristics Link a Bullet to a Manufacturer? J Forensic Sci Criminol 9(2): 203

Abstract

This paper was written to understand if there is a way to identify a bullet manufacturer based solely on the shape and characteristics of the bullet. Traditional methods of bullet identification are to use a bullet comparison microscope and look for toolmarks and rifling to link it to one particular gun. Cartridge case identification is a lot easier to link to the manufacturer being that there is already some identifying information of the breech face. These include but not limited to the bullet size (9mm), the gun manufacturer (SW-Smith and Wesson), and the trigger pin impression. This research is being done to find an alternative method of bullet identification in the event there are no cartridges left at a crime scene nor does the bullet have sufficient tool marks or rifling to link to a specific gun.

Keywords: Ballistics; Bullet Identification

History

The initial inquiry into bullet identification came about after legal professionals wanted to do away with the assumptions used in determining correlations between bullets and guns. Court cases involving questions of what gun fired the fatal round have been documented as far back as 1835 [1]. One example was in a Minnesota case where one of 2 suspect revolvers was used in a killing. A gunsmith was able to determine that one gun had true rifling and the other falsely rifled at the muzzle. From this, he gathered that the bullet most likely came from the revolver with true rifling.

In 1925, the Bureau of Forensic Ballistics was formed in New York City by Major Calvin H. Goddard Charles E. Waite, Philip O. Gravelle, and John H. Fisher [1]. Since most law enforcement agencies did not have their own Ballistics unit, they would call in the Bureau to investigate those matters. John H Fisher is also credited with being the first to modify and use a comparison microscope to analyze fired bullets and cartridge cases.

The Federal Bureau of Investigation (FBI) opened its own ballistic laboratory in 1932 [1]. Today, it is the biggest ballistics lab in the nation.

Over the next 45 years, several books were written explaining the science behind and techniques of bullet identification. It also continued to be a tool for convicting suspects in several court cases. Some high-profile examples being President John F. Kennedy, Lee Harvey Oswald, and Dr. Martin Luther King Jr.

Despite these advances, there is still skepticism in using bullet identification evidence in some courts [2]. Today, bullet identification is partially based in assumptions [3]. This causes problems when applying the Daubert Standard to this type of evidence [3]. Unlike DNA analysis, there isn't a method that yields a clear, definite, yes or no answer [3]. There are many Ballistics Examiners worldwide working to solve this problem.

Methods

Several scholarly articles were read through multiple search engines and used to provide a basis of information for creating this alternative method.

Results

Present methods of bullet identification involve comparing toolmarks on a bullet and a cartridge case [4]. Multiple types of comparison microscopes are used to identify these matches. Pattern matching is when the striations of two bullets, two cartridges, or one bullet and one cartridge are compared to see if they are a match [5]. Once the round is identified, the individual gun the round came from can be traced [5]. The gun that was used in the crime will then be examined and linked to the crimes' culprit. This method is not 100% accurate [7]. It depends on the examiner's level of experience and inference on what is considered a match. This method is widely considered to be the most effective by ballistics professionals.

Rifling is the spiral shape of indentions that form raised and lower areas (lands and grooves) inside the barrel. Toolmarks are markings caused by components of the gun hitting the bullet and casing during the usual process of firing a round or by striations the round obtains as it travels through the barrel. Striations are unique to one specific gun. Several instruments in a gun can create toolmarks. Trigger pin impressions are found on the breech face of the cartridge case. It forms when the trigger is pulled causing the pin to make contact with the breech face leaving an indentation. The ejection mark is formed when the ejector hits the cartridge and launches it out of the gun. Extractor marks are found around the rim of the cartridge. Anvil marks are found around the rim of rim fire cartridges (rounds that are ignited when the trigger pin hits the rim of the case) or the center of center fire cartridges (rounds that are ignited when the trigger pin hits the center of the case). Striations come from the imperfections that happen in

the manufacturing of gun parts [8]. The most useful striations come from the manufacturing of the barrel of the gun; where it gets all of its identifying features. When the round is ignited, the heat causes the metal to expand, allowing it to take on the rifling of the barrel along with any other stray marks that are inside it [8]. Magazine marks occur when the round as it is loaded into the chamber from the magazine [2]. The combination of these 2 types of toolmarks are compared in a bullet comparison microscope to see if they align [9].

Bullets can be made out of many different materials. The traditional metal for the core of a bullet is lead with cases made out of zinc and copper [10]. More modern bullets are made with bronze, aluminum, tin, steel, rubber, etc [11]. Primer is an explosive chemical compound that is used to ignite the combustible powder inside the case [12,13]. The compound is impact sensitive and compacted in a brass or copper alloy cup [14,15]. The modern version of gun powders also known as black powder is made up of sulfur (S), charcoal (C), and potassium nitrate (saltpeter, KNO_3) [16]. The charcoal and sulfur are the fuels of the bullet and the saltpeter is the bullet's oxidizer [17]. There are no specific details about bullet, primer, or powder components that could be linked to individual companies [18]. Information about the chemical components of manufacturers' ammunition was inaccessible.

Conclusion

Present methods of bullet identification involve comparing toolmarks on a bullet to the marks on a cartridge case. Pattern matching is when the striations of two bullets, two cartridges, or one bullet and one cartridge of compared to see if they are a match. This method is widely considered to be the most effective by ballistics professionals [19]. Rifling is the spiral shape of indentions that form raised and lower areas (lands and grooves) inside the barrel. Toolmarks are markings caused by components of the gun hitting the bullet and casing during the usual process of firing a round or by striations the round obtains as it travels through the barrel. Striations are unique to one specific gun. Several instruments in a gun can create toolmarks [20]. Based on the research done, there is not sufficient information publicly available to answer questions about bullet manufacturers' chemical formulas. After exhausting all research avenues, information on companies' specific metal percentages in bullets, primer components, chemical ratios, nor powder materials were found.

References

1. Hamby JE, Thorpe JW (1999) The History of Firearm and Toolmark Identification. *Association of Firearm and Tool Mark Examiners Journal* 31: 3.
2. Nichols R (2018) Firearm and Tool Mark Identification. *The Scientific Reliability of the Forensic Science Discipline* 121-34.
3. Grzybowski R, Miller J, Moran B (2003) Firearm/Toolmark Identification: Passing the Reliability Test Under Federal and State Evidentiary Standards. *AFTE Journal* 1-35.
4. Heizmann M, Puente León F (2001) Automated analysis and comparison of striated toolmarks. *European Meeting for Shoeprint/ Toolmark Examiners* 1-12.
5. Chu W, Thompson RM, Song J (2013) Automatic identification of bullet signatures based on consecutive matching striae (CMS) criteria. *Forensic Science International* 231: 137-41.
6. Goddard CH (1926) Scientific Identification of Firearms and Bullets. *Journal of Criminal Law and Criminology* 17: 1-11.
7. Schwartz A (2005) A Systemic Challenge to the Reliability and Admissibility of Firearms and Toolmark Identification. *The Columbia Science and Technology Law Review* 6: 1-42.
8. Jiong MFS (1995) Firearms Identification Using Pattern Analysis and Computational Modeling. U.S.N.A. --- Trident Scholar project report 228: 1-73.
9. Atchison RG (1995) Bullet cartridge casing identification system. United States Patent: US5685100A 1-8.
10. Cesaroni AJ (1996) Lead-free bullet. United States Patent: US6257149B1 1-10.
11. Walker JT (1940) Bullet Holes and Chemical Residues in Shooting Cases. *Journal of Criminal Law and Criminology* 31: 497-521.
12. Udey RN, Hunter BC, Smith RW (2011) Differentiation of Bullet Type Based on the Analysis of Gunshot Residue Using Inductively Coupled Plasma Mass Spectrometry*. *Journal of Forensic Science* 56: 1268-76.
13. Jomova K, Vondrakova D, Lawson M (2010) Metals, oxidative stress and neurodegenerative disorders. *Molecular and Cellular Biochemistry* 345: 91-104.
14. Brooks RC (1989) Methods of manufacturing a bullet. United States Patent: US00531123A 1-22.
15. Dobrowolska A, Melosik M (2008) Bullet-derived lead in tissues of the wild boar (*Sus scrofa*) and red deer (*Cervus elaphus*). *European Journal of Wildlife Research* 54: 231-5.
16. Bonfanti MS, De Kinder J, Members of the ENFSI Working Committee "3D Imaging" (1999) The influence of manufacturing processes on the identification of bullets and cartridge cases – a review of the literature. *Science & Justice Science & Justice* 39: 3-10.
17. Alfred K (1958) Electrical primers. United States Patent: US3019732A 1-3.
18. Chen D, Jiao X, Cheng G (1999) Hydrothermal synthesis of zinc oxide powders with different morphologies. *Solid State Communications* 113: 363-6.
19. Banno A, Masuda T, Ikeuchi K (2004) Three dimensional visualization and comparison of impressions on fired bullets. *Forensic Science International* 140: 233-40.
20. Collier WE (1994) Bullet Identification. United States Patent: US5646365A 1-9.

Submit your next manuscript to Annex Publishers and benefit from:

- ▶ Easy online submission process
- ▶ Rapid peer review process
- ▶ Online article availability soon after acceptance for Publication
- ▶ Open access: articles available free online
- ▶ More accessibility of the articles to the readers/researchers within the field
- ▶ Better discount on subsequent article submission

Submit your manuscript at

<http://www.annexpublishers.com/paper-submission.php>